

FIG. 1

Universal Intelligence Network (UniNet™)



FIG. 2

Private UniNet™ Networks



FIG. 3

UniNet nodes interconnected in a mesh structure





FIG. 4

Typical Near End and Far End Cross-talks Noise Environment



FIG. 5

TDM Transmit and Receive Flow cycles



FIG. 6

A UniNet Multicast Group



FIG. 7

UniNet Network over Plain Old Telephone Systems (POTS)



FIG. 8

Typical Parallel Channels for ECHO, NEXT and FEXT Cancellations



FIG. 9

UniNet Hierarchical Synchronization



FIG. 10

Gigabit Ethernet over 4 pairs of UTP cables



FIG. 11A

	3 dB Design	10 dB Design
Margin without FEXT	3.5 dB	10.7 dB
Margin with FEXT	2.5 dB	6.7 dB
Margin with FEXT + 3	1.8 dB	4.9 dB

FIG. 11B



FIG. 12A

Worst-case Insertion Loss of 100m, cat-5 Cable



FIG. 12B



FIG. 13A

Overall Return Loss of Different Cable Channel



FIG. 13B

Worst Case Return Loss Relative to Main Signal



FIG. 14
NEXT loss between pairs of cat-5 cables



FIG. 15

FEXT Loss Characteristics



FIG. 16
System Modeling



FIG. 17
Received (desired) pulse response



FIG. 18
Echo Pulse Response



FIG. 19A
NEXT Pulse Responses



FIG. 19B
NEXT Pulse Responses



FIG. 20A

Receiver Structure Using Interference Cancellers Prior to Equalizers



FIG. 20B

Receiver Using Interference Cancellers After FFE



FIG. 20C

Receiver using cascaded FSLE/DFE for
both interference suppression and equalization



FIG. 21

SNR versus Sampling Phase of different FFE/DFE configurations



FIG. 22

SNR versus Sampling Phase for various FSLE/DFE configurations



FIG. 23

SNR vs Sampling Phase



FIG. 24
Currently Proposed Structure



FIG. 25
Margin Offered by Different Schemes



FIG. 26

Improved-Performance Receiver Structure



FIG. 27

Receiver Structure using DPIC without NEXT cancellers



FIG. 28

Margin Offered by Various Schemes



FIG. 29

Existing SHDSL Transceiver Structure



FIG. 30

Proposed Transceiver Structure using DPIC



FIG. 31

SNR Measurement Points (A,B) (Proposed Transceiver Structure using DPIC)



FIG. 32

HDSL2 Front-End (Converter & Sampler & Equalizers)



FIG. 33A

SAE Developed De Long Network



FIG. 33B

SAE Developed De Long Network Impulse Response



FIG. 34

Next Generation 1553 System Modeling

FIG. 35

Current 1553 Architecture and Data Coding Scheme



Data Coding Scheme of Current 1553 Data Transmissions



Example of Current 1553 Bus Cabling Architecture (Redundant)



FIG. 36

Before and After Fractional Space Equalizer for Precursor ISI



100Mb/s USING PAM 8 over a 100m-cable

FIG. 37

Intersymbol Interference (ISI) at High Transmission Rate Over MIL-C17 Cable



FIG. 38

Decision Feedback Equalization to Remove Postcursor ISI



FIG. 39A

Proposed High Level 1553+ Transceiver Structure High Level



FIG. 39B

Proposed Medium Level 100Mb/s1553+ Transceiver Structure High Level



FIG. 39C

Proposed Detailed 100Mb/s 1553+ Transceiver Structure using DPIC



FIG. 40

Channelization/Timer Division Multiplex Access (TDMA/TDD)



FIG. 41

Com2000™ PAM-5 Partial Response Signaling Overview



FIG. 42

UniNet Internet Communication Processor

FIG. 43
Com2000™ Clock Transfer
Subsystem Block Diagram



FIG. 43A

Discipline Signal Generator





FIG. 43B
Oscillator Reference Clock Generator



FIG. 43C
Precision Reference Clock Generator



FIG. 43D
Measurement Source Selector



FIG. 43E
Corrected Output Generator



FIG. 43F
Com REF Clock Generator



FIG. 44
Com 2000™ Clock Transfer Control Logic



FIG. 45

Com2000™ LMS Adaptive Equalizer



FIG. 46

Com 2000™ State Transition Diagram

FIG. 47A

High Level UnitNet System Block Diagram



FIG. 47B UnitNet System Architecture Diagram





FIG. 48
Generic Tuning Algorithm

Intersymbol Interference



$s(t) - \sum_k a_k \sigma(t - K\tau_\sigma)$ $\quad \mu\tau(t)\text{-}g(t)\text{-}h(t)\text{-}c(t)$ $\quad y(t) - \mu\sum_k a_k \sigma(t - K\tau_\sigma) + n(t)$

The receiver filter output is sampled at time intervals $t_a = t\tau b$ giving

$$y(t_1) - \sum_{k=0}^{\infty} a_k P((t - K)T_o) + n(t_1)$$

$$- \mu\alpha_t + \mu\sum_{k=0}^{a} a_k P((i - K)T_o) + n(t_1)$$

FIG. 49
The ISI Definitions



FIG. 50
Conventional Forward and Decision Feedback Equalisers (FFE/DFE)

(20*6.25 us or 10 nodes in the UniNet network), as shown in figure 05



FIG. 51A

Phase Dependent Convergence of a FFE/DFE Filter

Performance of 51.84 Mb/s 16-CAP transceiver over 100 m category 3 cable with one cyclostationary NEXT interferes

TIA/EIA NEXTR model a = 1.2 1/T = 12.96 Mbauch $P_2 = 10^{-10*}$

$\phi 1$ (i T/δ)	SNR_i (dB)	SNR_1 (dB)	SNR_n (dB)	Margin (dB)
ϕ_0	12.5	13.0	54.9	31.65
ϕ_1	12.5	14.8	58.1	43.85
ϕ_2	12.5	18.3	61.3	38.05
ϕ_3	12.5	18.4	61.9	38.65
ϕ_4	12.5	14.8	60.5	37.35
ϕ_5	12.5	13.0	57.1	33.85

*Margins are with respect to $P_2 = 10^{-10}$ for which $SNR_{0,mf} = 23.23$ dB

FIG. 51B

Phase Dependent Convergence of FFE/DFE Filter - SNR



FIG. 52A

The Eye Open Diagram of Biphase Manchester, MLT3 and PAM5



FIG. 52B

The Signal Spectrum and Eye Open Diagram of SPAM5



FIG. 53

The ECHO and NEXT Canceller Filter Performance



FIG. 54
Precision Phase Angle Controls



FIG. 55
Time, Phase, Frequency Division Multiple Access Signal Coding Scheme



FIG. 56
The Gigabit Com2000™ PHY
Functional System Block Diagram



FIG. 57
Coherent Carrier Recover PLL Loop for UniNet Receiver



FIG. 58
General Frame Structures



FIG. 59
Downstream and Upstream Sections



FIG. 60
Simplified Burst and Cell Structures



FIG. 61
Time Relationship between various Frame Markers



FIG. 62
Tx Frame Gating Signal

Sampling Phase or Error Vector Measurement (EVM)



FIG. 63
Rx Formatter



FIG. 64
IP Packet Network Processing Functions



FIG. 65
Distributed Packet Switching Architecture



FIG. 66
UniNet Application over Existing Ethernet IP Networks

FIG. 67A/B


Begin Node Measurement
7b01
Determine # of Bytes Sent/Min/Node For All Nodes
7b02
Establish Node Priority Based On Bytes/Min
7b03
Modify Priority Based On Node Traffic Group Assignment
7b04
Modify Priority Based On Node Application Priority Level Assignment
7b05
Determine Maximum TmX Transmit Time For Each Node
7b06
Calculate Optimal MTU Size For Each Node
7b07
Calculate TCP/IP Collision Window From TmX and MTU Size
7b08
Update Time Slice Schedule
7b09
Broadcast Transmission Device Control Parameters
7b10
Begin Server Scheduler
7b11

FIG. 67C

DIPA/TDDA Algorithm





FIG. 67D
DIPA/TDDA Algorithm

FIG. 67E

TDDA Algorithm





FIG. 67F

TDPA Algorithm





FIG. 67G
CSOA Algorithm

FIG. 67H/I

E-DNA Derived Key with 56 bits DES and Scrambled 64 Data bits



FIG. 67J/K

Expected Receiving Parameters Dependent DES Key Generation



FIG. 67L

Outline of the compression function of RIPEMD-160.
Inputs are a 16 word message block Xi and a 5-word chaining variable h0h1h2h3h4, output is a new value of the chaining variable





FIG. 68

UniNet Communication Processor System Block Diagram



FIG. 69A

Baseband Converter and Sampler
(Receiver Only View for Wireless)



FIG. 69B
Baseband Processor

FIG. 70

PoR Prototype System for Applications using POTS as Communications Media



FIG. 71

Block Diagram of the Prototype



FIG. 72

Ethernet Interface and Buffer Management





FIG. 73
DCA Block & Interface Diagram

FIG. 74
DCA Assignment Processes



FIG. 75

Packetizer Block Diagram





FIG. 76
Multi-Frame Format



FIG. 77
Frame Format



FIG. 78
Burst Format



FIG. 79
TDMA Controller Interface



FIG. 80
TDMA Controller Interface



FIG. 81
Rx Framer Block Diagram

FIG. 82
Flow Chart of The Receive Frame Synchronizer





FIG. 83
TX Framer Block Diagram



FIG. 84
TX Framer Controller



FIG. 85
Burst-Mode Modern Block Diagram



FIG. 86
Block Diagram of Burst-Mode MOD



FIG. 87
Block Diagram of Equalizer



FIG. 88
Block Diagram of Burst-Mode DEMOD



FIG. 89

Synchronizer Block & Interface Diagram



FIG. 90
Analog Front-End Block Diagram